


- Real 2.500 bar operating pressure, 6.250 bar burst pressure
- Made from polyflex material, slim and flexible design
- 6 spiral layers of high tensile steel wire covered by plastic
- Suitable production with international safety criteria
- High strength, suitable for use in hydraulic oil and water
- Low volumetric expansion 8,4%, length change +%1/-%2
- Made in Germany, brand Parker with CE marking



Model No	 Working Pressure		 Burst Pressure		 Inner D-Outer D.		 Bend Radius	 Weight
**	bar	psi	bar	psi	mm	mm	mm	kg/m
2640D-03V32	2.500	36.250	6.250	90.625	4,7	13	175	0,41



Model	2640D-03V32
Working Pressure	2.500 bar
Burst Pressure	6.250 bar
Safety Factor	1:2,5
Inner Diameter	4,7 mm +0,2 mm (3/16")
Outer Diameter	13,0 mm -0,1mm
Bend Radius	175 mm
Inner Core	POM
Pressure Reinforcement	6 spiral layers of high tensile steel wire
Outer Cover	PA-12 / Blue
Change in Length at max.	+1 % / -2%
Volumetric Expansion at max.	8,4 %
Impulse Strength	≥ 30.000 impuls cycles
Working Temperature	-40 C° + 100 C°