BOTTLE JACKS

2-110 Ton

Portable hydraulic power





INDUSTRIAL LIFTING AND PUSHING APPLICATIONS.

- Choose from this complete line of premium-quality, standard bottle jacks. Ideal for use in any number of industrial lifting and pushing applications.
- The 9110B, 9015B, 9022B and 9033B feature a beveled base which allows the jack to "follow" the load, reducing the chance of dangerous side-loading.
- Many jacks feature screw extensions
- All jacks can be used in the vertical, angled or horizontal positions.
- Serrated or contoured saddles help stabilize the load for a safer lift.
- All jacks meet ASME B30.1 standards and carry the Power Team Marathon Lifetime Warranty.
- 110-ton jack features dual pumps for time-saving two-speed operation.



ORDERING INFORMATION*												
			Retracted Height	Length of Screw	Height w/Screw	No. Pump Strokes to		Base	Pump Handle	Handle Effort at		Product
Cap.	Stroke	Order	Min.	Ext.	Ext.	Ext. Piston	Dia.	Size	Length	Rated Cap.	Carry	Weight
Tons	(in.)	Number	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(in.)	(lbs.)	Handle	(lbs.)
2	$4^{1}/_{2}$	9002A	71/8	$1^{15}/_{16}$	139/16	5	1	$4^{11}/_{32} \times 2^{9}/_{16}$	121/4	75	No	4.8
3	$4^{1}/_{2}$	9003A	$7^{1}/_{2}$	$2^{3}/_{8}$	143/8	10	$1^{1}/8$	$4^{1}/_{2} \times 2^{27}/_{32}$	191/4	45	No	5.8
5	$4^{3}/_{4}$	9005A	$7^{7}/8$	$2^{3}/_{4}$	$15^{3}/_{8}$	12	13/8	5³/ ₁₆ x 3	217/16	55	No	8
8	$4^{3}/_{4}$	9008A	$7^{7}/8$	$2^{3}/_{4}$	15 ³ / ₈	18	$1^{1}/_{2}$	$6 \times 3^{1}/_{2}$	2313/16	75	No	12.1
12	$5^{7}/8$	9112A	$9^{1}/_{2}$	31/8	$18^{1}/_{2}$	26	17/8	$6^{1}/_{2} \times 4^{3}/_{16}$	2313/16	60	Yes	17.5
15	$6^{1}/_{8}$	9015B	$9^{1}/_{16}$	$4^{1}/_{2}$	$19^{7}/8$	27	$2^{3}/8$	$5^{1}/_{8} \times 5^{1}/_{2}$ †	279/16	90	No	18.3
20	$6^{1}/_{4}$	9120A	105/8	35/8	$20^{1}/_{2}$	22	2	$7^3/_{16} \times 5^1/_{16}$	$31^{1}/_{2}$	70	Yes	28.5
22	61/8	9022B	$9^{7}/_{16}$	45/16	$20^{1}/_{2}$	36	$2^{3}/8$	$6^{1}/_{2} \times 6^{5}/_{16}$ †	279/16	90	Yes	23.6
30	$6^{1}/_{4}$	9030A	11	_	171/4	35	$2^{3}/8$	$7^9/_{16} \times 5^9/_{16}$	$39^{3}/_{8}$	50	Yes	41.2
33	5 ⁵ /8	9033B	$9^{7}/_{16}$	$4^{3}/_{16}$	$19^{3}/_{4}$	56	29/16	$7^{1}/_{4} \times 6^{15}/_{16}$ †	279/16	88	Yes	32
50	$6^{3}/_{4}$	9050A	12	_	183/4	35	3	$9^{5}/_{16} \times 7^{3}/_{8}$	$39^{3}/_{8}$	85	Yes	78
110	61/8	9110B	1113/16	_	1715/16	40/160‡	$4^{3}/_{8}$	13 ³ / ₈ x 11 ⁷ / ₁₆	279/16	79	Yes	154.3

^{*}See current price list for shipping weights.

[†] Comes with a Beveled Base

^{† 2} Speed: Rapid advance≈40 strokes; Lift mode≈160 strokes