JDN RATCHET HOISTS WITT

Carrying capacities: 1.5 t, 2.5 t

The **WITT** is designed for for lifting, pulling, tensioning or anchoring operations under all working positions. It has a robust cast iron housing and is extremely resistant to adverse working conditions. Technically the **WITT** distinguishes itself by a totally enclosed planetary gear. All rotating parts have ball, needle or slide bearings.

The **WITT** is a proven device for moving and positioning heavy machinery, for tensioning heavy loads during transport, for positioning various heavy profiles and for many other operations.



■ TECHNICAL DATA

Туре		WITT 1,5t	WITT 2,5t
Carrying capacity	mt	1.5	2.5
Number of falls			l
Lift per ratchet rotation	inch.	1.3	1.5
	mm	33	<i>37</i>
Lever force at full load	lbs	61.7	88.2
	kg	28	40
Weight without chain	lbs	16.5	39.7
	kg	7.5	18
Total weight	lbs	20.3	48.5
	kg	9.2	22
Weight of 1 m chain	lbs	2.2	6.0
	kg	1	2.7
Chain dimension	mm	7.1 x 21	11 x 31
Standard lift	ft m	59.1 <i>1.5</i>	

DIMENSIONS

Туре		WITT 1,5t	WITT 2,5t
A smallest headroom	inch.	13.6	17.3
	mm	<i>345</i>	440
В	inch.	6.3	7.3
	mm	160	185
С	inch.	2.6	2.8
	mm	65	<i>7</i> 2
D	inch.	3.7	5.5
	mm	93	140
Е	inch.	1.1	1.2
	mm	27	31.5
F	inch.	14.4	15.6
	mm	365	<i>3</i> 95
G	inch.	3.7	5.2
	<i>mm</i>	95	133
Н	inch.	2.4	3.5
	mm	62	88

